CARROT MAESTRO

AN EXCEPTIONALLY HIGH YEILDING MAIN SEASON VARIETY

- High potential pre-pack percentage
- Uniform cylindrical and well-rounded roots
- High silvering tolerance
- Outstanding shelf appearance
- · High leaf disease resistance



Туре

F1 Nantes hybrid.

Maturity

115 - 125 days (summer), 125 - 155 days (winter).

Plant Characteristics

Leaf Characteristics: Dark green colour, medium to long length, upright growth habit and a strong attachment. **Root Characteristics:** 16 – 18 cm root length, cylindrical root shape, deep orange colour and exceptionally smooth texture with no silvering.

Variety Characteristics

Bolting: Negligible bolting under extremely hot conditions.

Growing Guidelines: Sowing: Ensure good seedbed preparation prior to sowing. Pre-pack carrots: 1.0 – 1.8 million seeds per hectare.

Features & Benefits

Silvering tolerance – provides extended visual presentation on the shelf.

Market Segment: Fresh market, pre-pack and bunching.

In-situ Storability: Good storability.

Disease Resistance: HR: Alternaria dauci and Powdery Mildew.

IR: Cavity Spot.

Disclaimer: This information is based on our observations and/or information from other sources. As crop performance depends on the interaction between the genetic potential of the seed, its physiological characteristics, and the environment, including management, we give no warranty express or implied, for the performance of crops relative to the information given nor do we accept any liability for any loss, direct or consequential, that may arise from whatsoever cause. Please read the Starke Ayres Standard Terms and Conditions of Sale before ordering seed.

Resistance: is the ability of a plant variety to restrict the growth and development of a specified pest or pathogen and/or the damage they cause when compared to susceptible plant varieties under similar environmental conditions and pest or pathogen pressure. Resistant varieties may exhibit some disease symptoms or damage under heavy pest or pathogen pressure (HR = High resistance, IR = Intermediate resistance).